



# Wood Trails

Glazed Ceramic Tile  
High Density Ceramic



## Technical Data



### Tile Applications: Residential Light Commercial Commercial

Floors	•		
Walls/backsplashes	•	•	•
Countertops	•	•	•

\*Not recommended for ramps or floor areas exposed to water or heavy grease accumulation

Property:	Results	ASTM	ASTM #:
Wear Rating (PEI)	III	0-V	ASTM C1027
Chemical Resistance	Resistant	As reported	ASTM C650
Bonding Strength (psi)	>50	>=50	ASTM C482
Dynamic Coefficient of Friction	<0.42	As reported	ANSI A 137.1-2012
Scratch Hardness	7.0	>=5.0	EN 101
Water Absorption	<3.00%	>3	ASTM C373
Breaking Strength	>350 lbs.	>300	E.N. ISO 13006
Frost Resistance	Resistant	Resistant	ASTM C1026
Stain Resistance	Resistant	As reported	ASTM C1378
Crazing Resistance	Resistant	Resistant	ASTM C424
Thermal Shock	Resistant	Resistant	ASTM C484

### Glacier White



6" x 20"

### Pinnell Beige



6" x 20"

### Appalachian Brown



6" x 20"

### Batona Gray



6" x 20"